

## High-frequency Sieve Shaker



### High-frequency Sieve Shaker

- **Application:** Used for graded analysis of non-cohesive and dry grain substances.
- **Model:** MSSS6ASTMSWISS
- **Frequency:** 500 times/min
- **Shaking Method:** Up and down
- **Shaking Amplitude:** 1.5 mm
- **Time Setting:** 0 – 60 min (selectable)
- **Sieve Size Options:**
  - Ø200 x 50 mm (9 pieces)
- **Sieve Opening:** 20 – 0.075 mm
- **Power Supply:** 220 V, 50 Hz
- **Dimensions:** 430 x 430 x 750 mm
- **Noise Level:** ?50 dB
- **Amplitude:** ?5 mm

- **Speed:** 1450 r/m
- **Power Consumption:** 0.125 kW
- **Input Quantity:** ?200
- **Weight:** 40 kg

ASTM Test Sieves come in below diameters:

- a) 3in (76mm)
- b) 6in (152mm)
- c) 8in (203mm)
- d) 10in (254mm)
- e) 12in (305mm)

#### **Product: Stainless Steel Test Sieves**

- **Standard:** BS 410
- **Material:** Stainless steel/brass
- **Sieve Diameter:** 200 mm / 300 mm / Customizable
- **Height:** 50 mm
- **Compliance Standards:** ISO, EN, BS, and ASTM sieves